

# **METALFORM**

**MASTERS OF METAL**

**EBE 85 Inward and outward opening doors | tilt  
and turn | burglar-proof RC3 | In corten steel**

# METALFORM

## EBE 85 Inward and Outward Opening Doors | Tilt and Turn | Burglar-Proof RC3 | In Corten Steel

### Description:

Supply and installation of doors, windows, and facades featuring fixed and openable sashes, designed for inward and outward opening configurations. Built with thermal break profiles, specifically Secco Sistemi EBE 85.

### Construction:

- Frame sections composed of two seamlessly joined metal shells, one internal and one external, filled with extruded polyamide infused with fiberglass and bonded with high-density polyurethane resin.
- Metal shells crafted from cold-rolling profiling strips of Cor-Ten steel (Fe510X) with a thickness of 15/10, meeting standard EN1049.
- Folding unit designed to facilitate insertion of stainless steel alignment brackets, even with continuous surface welding.
- Assembly of frames involves continuous welding of contact surfaces, followed by grinding and restoration of surface finish.

### Design Details (Windows):

- Windows feature internal overlap and external coplanarity profiles.
- Visible sections include fixed side node of 47 mm, openable side node of 85 mm, central node for the two panels, asymmetrically measuring 107mm or symmetrically measuring 145mm, with a mandatory depth of 85 mm.
- Water, air, and wind sealing system for inward opening windows includes triple mortise gasket with two sealing levels, one of which is open-joint. Outward opening windows and doors feature double mortise gasket providing a closed joint seal.
- Mobile sill for floors included with doors.
- Corten steel screw-on water drains provided in the windows.

# METALFORM

## Glazing:

- Frames equipped with glass (type to be specified) fixed with glazing beads, available in options such as Squared, Gothic, or Thin.
- Glazing beads made of Corten steel, spaced from external surfaces by EPDM or silicone gaskets, and from internal surfaces by pressure-inserted EPDM gaskets.

## Hardware (Windows):

- Windows equipped with concealed, screw-on hot burnished stainless steel hinges, adjustable with three wings (Ø15 mm, 180kg capacity per panel).
- Alternatively, windows feature tilt and turn openings with perimeter hardware, available with either concealed hinges (130 kg load capacity) or visible hinges (Ø14 mm, 150 kg load capacity), equipped with an appropriate number of locking points depending on the sash size.

## Burglar-Proofing:

- Windows have an RC3 certified burglar alarm category.

## Hardware (Doors):

- Doors equipped with locks featuring an appropriate number of locking points proportioned with the height of the sashes.
- Adjustable screw-on stainless steel hinges provided for load capacities up to 250 kg (Ø21.5 mm), and for load capacities up to 160 kg (Ø22.5 mm) in Corten steel.

## Surface Finish:

- Surfaces oxidized and finished with acid etching, oxidation, passivation, and waxing processes.

## Handles:

- Handles available in various shapes, materials, and finishes, including Corten steel.

# METALFORM

MASTERS OF METAL

**UNITED KINGDOM**

**METALFORM**

**NORWAYMETAL LTD**

53 Chelsea Manor Street

London, SW3 5RZ

**SALES@METALFORM.UK**

**+44 20 81298814**

**GERMANY**

**METALFORM GMBH**

Carl-Zeiss-Ring 15A

85737 Ismaning

**SALES@METALFORMGROUP.DE**

**+49 17663630406**

**NORWAY**

**METALFORM AS**

Brochmannsveien 2

1950 Rømskog

**SALG@METALFORM.NO**

**+47 401 62 446**

**METALFORMGROUP**

**SALES@METALFORMGROUP.COM**